

MRBAT168

MediaRange Rechargeable USB-C Li-Ion Batteries, Baby C I 1.5V I 4.500mWh I 3.000mAh, 2-Pack

MediaRange rechargeable Li-Ion batteries provide a constant 1.5V output for compatible devices using Baby C batteries. Thanks to the integrated USB-C charging port, the batteries can be charged directly with the supplied USB-A to 2x USB-C charging cable without the need for a separate battery charger.

Each battery provides a rated output capacity of 3,000mAh / 4,500mWh and can be recharged up to 1,200 times[1]. Integrated protection mechanisms protect against overcharge, over-discharge, short-circuit and overcurrent.

The supplied charging cable allows both batteries to be charged simultaneously from a suitable USB-A power source. The integrated LED indicator flashes during charging and remains steadily lit when the battery is fully charged.

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D - 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

MediaRange

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D – 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

FEATURES

- Batteriegröße: Baby C
- Dimensions: approx. Ø 26 x 50 mm
- Weight: approx. 47g per battery
- Rechargeable Li-Ion battery
- Constant output voltage: 1.5V
- Rated output capacity: 3,000mAh / 4,500mWh
- Internal battery cell: Li-Polymer, 3.7V / 1,350mAh / 4,950mWh
- USB-C charging input: 5V?500mA max.
- Charging time: approx. 2 hours
- Rechargeable up to 1,200 times[1]
- LED charging indicator: flashing while charging, steady when fully charged
- Continuous discharge current: 200mA
- Integrated protection against overcharge, over-discharge, short-circuit and overcurrent
- Direct charging via integrated USB-C port
- No separate battery charger required
- USB-A to 2x USB-C charging cable included
- Suitable for compatible devices designed for 1.5V Baby C batteries

APPLICATIONS

Suitable for compatible devices requiring 1.5V Baby C batteries, such as: Flashlights and portable lighting, Toys and electronic devices, Radios and audio devices, Measuring and monitoring equipment, as well as other compatible battery-powered devices.

CONTENTS OF PACKAGING

- 2x Rechargeable 1.5V Baby C Li-Ion batteries
- 1x USB-A to 2x USB-C charging cable
- 1x User manual and safety instructions

APPLICATIONS

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D – 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

IMPORTANT INFORMATION Read the user manual carefully and follow the safety instructions before use. For optimal performance, fully charge the batteries before first use. [1] Performance and the achievable number of recharge cycles may vary depending on usage and environmental conditions. The battery contains an internal Li-Polymer cell with a nominal voltage of 3.7V. The output is electronically regulated to a constant 1.5V for use in compatible devices. Do not use conventional Ni-MH or Ni-Cd battery chargers. Charge the batteries only via the integrated USB-C charging port. Do not charge the batteries while they are in use.

SAFETY INFORMATION Read instructions before use. Keep out of reach of children. Do not swallow. Do not deform or damage. Do not insert incorrectly. Do not open or dismantle. Do not mix different types or brands. Do not subject to strong impact. Do not mix new and used batteries. Insert correctly and observe polarity (+/?). Do not dispose of in fire.

EAN Code Piece:4262543442488

EAN Code Carton:4262543442495

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D - 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de