MRMA116-UK

MediaRange 65W GaN Fast Charging Adapter (UK-Plug), 2x USB-C and 1x USB-A, USB-C® Power Delivery and Quick Charge™ enabled, White

Efficient multi-device charging from a single outlet

The MediaRange 65W GaN fast charging adapter is designed for efficient and reliable charging of mobile devices via standard electrical outlets. It enables simultaneous charging of up to three devices using two USB-C ports and one USB-A port.

Advanced GaN technology for compact design and thermal efficiency

Advanced GaN (Gallium Nitride) technology allows a compact and lightweight design while reducing heat generation during operation. Intelligent integrated chipsets continuously monitor charging power and temperature throughout the entire charging process to ensure stable and safe charging performance.

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D - 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

Support for modern fast charging standards

The charging adapter supports latest fast charging technologies, enabling compatible devices to be charged efficiently according to their individual power requirements. It is suitable for charging smartphones, tablets, USB-C–powered laptops, wearables and other mobile devices.

Durable housing design and integrated protection mechanisms

The adapter features a shock- and fire-resistant V0-rated polycarbonate housing and is equipped with comprehensive protection mechanisms including overvoltage, overcharge, short-circuit and overheating protection for reliable everyday use.

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D - 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

FEATURES

Key Features

- 65W GaN fast charging adapter with UK Type G plug
- Supports USB-C® Power Delivery 3.0, PPS (Programmable Power Supply) and Quick Charge™ 3.0[1]
- Two USB-C ports and one USB-A port for simultaneous charging of up to three devices[2]
- USB-C1 supports up to 65W output when used individually
- Advanced GaN technology for compact design and reduced heat generation
- Intelligent chipsets for continuous monitoring of charging power and temperature
- Overvoltage, overcharge, short-circuit and overheating protection
- Shock- and fire-resistant V0-rated polycarbonate housing

Technical Data

- Input voltage / frequency / current: AC 100–240V, ~50/60Hz, 1.5A (max.)
- Total output power: 65W (max.)
- Plug type: UK Type G (BS 1363)
- Output voltage / -current / -power:
  - USB-C1 (Power Delivery 3.0): 5.0V ? 3.0A (15W) / 9.0V ? 3.0A (27W) / 12.0V ? 3.0A (36W) / 15.0V ? 3.0A (45W) / 20.0V ? 3.25A (65W max.)
  - PPS (Programmable Power Supply): 3.3–11.0V ? 5.0A (55W max.)
  - USB-C2 (Power Delivery 3.0): 5.0V ? 3.0A (15W) / 9.0V ? 2.22A (20W) / 12.0V ? 1.67A (20W max.)
  - USB-A (Quick Charge 3.0): 5.0V ? 3.0A (15W) / 9.0V ? 2.0A (18W) / 12.0V ? 1.5A (18W max.)
- Combined output power:
  - USB-C2 + USB-A: 5.0V ? 3.0A (15.0W max.)
  - USB-C1 + USB-C2: 45W + 18W (63W max.)
  - USB-C1 + USB-A: 45W + 18W (63W max.)
  - USB-C1 + (USB-C2 + USB-A): 45W + (5.0V ? 3.0A) (60W max.)
- Average efficiency during operation: 80.40%
- Efficiency at low load (10%): 74.57%
- Power consumption at zero load: 0.157W
- Color: White
- Dimensions / Weight: 85.7 × 50.2 × 41.3 mm / 123.2 g

Included in the Box

- Charging adapter

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D – 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de

- User manual and safety instructions

APPLICATIONS

Notes & Footnotes

[1] Fast charging requires compatible devices, chargers and suitable charging cables.

[2] When charging multiple devices simultaneously, output power is dynamically distributed and charging speed may be reduced.

Please read and follow the included user manual and safety instructions before use. Charging speed depends on the connected device, cable quality and operating conditions. Charging cables for end devices are not included. All technical specifications are based on internal records and tests under controlled conditions. All products and illustrations mentioned are subject to change. The illustrations shown may differ from the actual product. Technical changes as well as errors and misprints are reserved. USB-C® and USB Power Delivery® are registered trademarks of the USB Implementers Forum. Quick Charge™ is a trademark of Qualcomm Incorporated.

EAN Code Piece:4262543441542

EAN Code Carton:4262543441559

MediaRange GmbH
Geschäftsführung: Markus Speer, Max Eckhardt

Straße: Zum Quellenpark 29
Ort: D - 65812 Bad Soden

Tel.: +49 (0)61 965 2381 80
Fax: +49 (0)61 965 2381 89

Internet: www.mediarange.de
E-Mail: info@mediarange.de